



Hydrostatic Pipeburster - model T65

Close-up

Hydrostatic Pipeburster - model T65

The T65 Pipeburster with its 65 tonnes static pull back power, is capable of replacing existing pipes from; Ø 40 mm up to Ø 300 mm.

Being one of the narrowest models on the market, the T65 is a highly flexible unit which can be used where similar classed machines are too wide.

T65 is remote controlled and mounted with a built-in emergency strike system for safety. Further more, the machine is fitted with a unique fully automatic “two-speed control system” This system allows the unit to operate in high speed mode when pushing or pulling the steel rod system through the existing pipe.

Technical specifications:

	T65 Pipeburster	T65 Power pack
Length:	2.10 meter	1.50 meter
Width:	0.40 meter	0.95 meter
Height:	0.80 meter	0.98 meter
Weight:	1.150 kg	550 kg

The T65 Pipeburster operates with two sizes of solid steel rod systems; Ø 50 mm as standard and the smaller Ø 35 mm. system which allows the machine to replace pipes as small as 40 mm.

The recommended maximum length of replacing an existing pipe is 150 meters. All steel rods are threaded in both ends and handled by a fully automatic unit called; “ARD65” The automatic rod device spins the rods on and off and thereby minimizes any manual work whilst handling the round rods.

The ARD65 is powered by the T65 power pack. Approximately one hour is used to replace 100 meters of any existing pipe.

Recommended dimensions for the T65 Pipeburster excavation:

Length:	4.00 meter
Width:	1.00 meter
Depth:	0.20 meter “below centre line of existing pipe”

