



Hydrostatic Pipeburster - model T85

Close-up

Hydrostatic Pipeburster - model T85

The T85 Pipeburster with its 85 tonnes static pull back power, is capable of replacing existing pipes from;
 Ø 75 mm. up to Ø 400 mm.

Being one of the most power full and compact mid-range pipebursters on the market the T85 caters for a large percentage of work available in the industry. The T85 is fitted with a double set of hydrostatic jaws which makes it possible to replace up to 250 meters in one single operation.

T85 is remote controlled and mounted with a built-in emergency strike system for safety. Further more; the machine is fitted with a unique fully automatic "two-speed control system" This system makes the unit able to operate in a high speed mode when pushing or pulling the steel rod system through the existing pipe.

Technical specifications:

	T85 Pipeburster	T85 Power pack
Length:	1.80 meter	2.10 meter
Width:	0.70 meter	1.35 meter
Height:	1.10 meter	1.25 meter
Weight:	3.200 kg	1.450 kg

The T85 Pipeburster operates with 50 mm solid steel rods as standard.

All steel rods are threaded in both ends and handled by a fully automatic unit called; "ARD85" The automatic rod device spins the rods on and off and thereby minimizes any manual work whilst handling the round rods.

The ARD85 is powered by the T85 power pack.

Approximately one hour is used to replace 100 meters of any existing pipeline.

Recommended dimensions for the T85 Pipeburster excavation:

Length:	3.00 meter
Width:	1.30 meter
Depth:	0.35 meter "below centre line of existing pipe"

